



SPROCKETS AUSTRALIA PTY LTD

SPROCKETS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 100

31,75 x 19,05 mm

Roller 19,05 mm



B1	B2	B3	b1	C	r3
17,6				4	33,5

Z	de	dp	Simplex			Kg.
			dm	D1	A	
8	96,0	82,96	53	20	40	0,85
9	106,5	92,84	63	20	40	1,18
10	117,0	102,74	70	20	40	1,57
11	127,0	112,68	77	20	45	2,04
12	137,0	122,68	88	20	45	2,58
13	147,5	132,65	98	20	45	3,15
14	157,6	142,68	108	20	45	3,78
15	167,7	152,72	118	20	45	4,47
16	177,7	162,75	120	25	50	5,25
17	187,7	172,78	120	25	50	5,61
18	197,8	182,85	120	25	50	5,99
19	207,9	192,91	120	25	50	6,40
20	217,9	202,98	120	25	50	6,82
21	228,0	213,04	140	25	55	8,79
22	238,1	223,11	140	25	55	9,27
23	248,2	233,17	140	25	55	9,77
24	258,3	243,23	140	25	55	10,30
25	268,4	253,33	140	25	55	10,85
26	278,4	263,40				
27	288,5	273,48				
28	298,5	283,56				
29	308,6	293,65				
30	318,7	303,75				
31	328,8	313,85				
32	338,9	323,91				
33	349,0	334,01				
34	359,1	344,10				
35	369,2	354,20				
36	379,2	364,30				
37	389,3	374,39				
38	399,4	384,49				
39	409,5	394,59				
40	419,6	404,66				

Please note: Length through bore and bore size may vary from time to time.

