



SPROCKETS AUSTRALIA PTY LTD

SPROCKETS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 140

44,45 x 25,4 mm
Roller 25,4 mm



B1	B2	B3	b1	C	r3
23,5				5,8	47,5

Z	de	dp	Simplex			Kg.
			dm	D1	A	
8	132,0	116,15				
9	146,0	129,96				
10	160,0	143,85	100	25	70	5,23
11	174,0	157,77	112	25	70	6,53
12	188,0	171,74	125	25	70	8,02
13	204,0	185,75	125	25	70	8,72
14	218,0	199,76	125	25	70	9,46
15	232,0	213,79				
16	246,0	227,84	160	30	75	14,65
17	260,0	241,90	160	30	75	15,50
18	274,0	255,98				
19	289,0	270,06				
20	303,0	284,15				
21	317,0	298,24				
22	331,0	312,34				
23	345,0	326,44				
24	359,0	340,55				
25	373,0	354,66				
26	387,0	368,77				
27	401,0	382,88				
28	416,0	397,00				
29	430,0	411,12				
30	444,0	425,24				
31	458,0	439,37				
32	472,0	453,49				
33	486,0	467,62				
34	500,0	481,75				
35	514,0	495,88				
36	529,0	510,01				
37	543,0	524,13				
38	557,0	538,27				
39	571,0	552,40				
40	585,0	566,54				

Please note: Length through bore and bore size may vary from time to time.

