



SPROCKETS AUSTRALIA PTY LTD

SPROCKETS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 25

6,35 x 3,18 mm
Roller 3,3 mm



B1	B2	B3	b1	C	r3
2,9				0,6	6

Z	de	dp	Simplex			Kg.
			dm	D1	A	
8	18,1	16,59				
9	20,2	18,56				
10	22,3	20,55	12	6	15	0,02
11	24,3	22,54	14	6	15	0,02
12	26,4	24,53	16	6	15	0,03
13	28,5	26,53	18	6	15	0,03
14	30,5	28,53	20	6	15	0,04
15	32,5	30,55	22	6	15	0,05
16	34,5	32,55	24	8	15	0,06
17	36,5	34,55	26	8	15	0,07
18	38,5	36,56	28	8	15	0,08
19	40,5	38,58	30	8	15	0,09
20	42,5	40,58	32	8	15	0,10
21	44,6	42,60	34	8	15	0,11
22	46,6	44,62	36	8	15	0,12
23	48,6	46,63	38	8	15	0,14
24	50,6	48,64	40	8	18	0,18
25	52,6	50,66	42	8	18	0,20
26	54,6	52,67				
27	56,6	54,69	46	10	18	0,22
28	58,7	56,71	48	10	18	0,25
29	60,7	58,73				
30	62,7	60,75	48	10	18	0,27
31	64,7	62,76				
32	66,7	64,78	50	12	18	0,29
33	68,8	66,80				
34	70,8	68,82	50	12	18	0,28
35	72,8	70,84	50	12	18	0,30
36	74,8	72,85	50	12	18	0,31
37	76,8	74,87				
38	78,8	76,89				
39	80,9	78,91				
40	82,9	80,93				

Please note: Length through bore and bore size may vary from time to time.

