




# SPROCKETS AUSTRALIA PTY LTD

SPROCKETS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

## ASA 35

9,525 x 4,77 mm  
Roller 5,08 mm

B1	B2	B3	b1	C	r3
4,3	14,3		4,1	1,2	10



Z	de	dp	Simplex				Duplex			
			dm	D1	A	Kg.	dm	D2	A	Kg.
8	28,6	24,89								
9	31,5	27,85	18	8	20	0,05				
10	34,5	30,82	20	8	20	0,05				
11	37,5	33,80	22	8	25	0,08				
12	40,5	36,80	25	8	25	0,10				
13	43,5	39,80	28	8	25	0,12	28	10	30	0,16
14	46,5	42,80	31	8	25	0,15	31	10	30	0,19
15	49,5	45,81	34	8	25	0,19	34	10	30	0,23
16	52,5	48,82	37	10	28	0,24	37	12	30	0,27
17	55,5	51,83	40	10	28	0,28	40	12	30	0,31
18	58,6	54,85	43	10	28	0,32	43	12	30	0,36
19	61,6	57,87	45	10	28	0,36	46	12	30	0,42
20	64,6	60,89	46	10	28	0,38				
21	67,6	63,91	48	12	28	0,41	52	16	30	0,51
22	70,6	66,93	50	12	28	0,45	55	16	30	0,57
23	73,7	69,95	52	12	28	0,49	58	16	30	0,64
24	76,7	72,97	54	12	28	0,54	61	16	30	0,71
25	79,7	76,00	57	12	28	0,60	64	16	30	0,78
26	82,7	79,02								
27	85,7	82,04	60	12	28	0,67	70	16	30	0,94
28	88,8	85,07	60	12	28	0,68	73	16	30	1,02
29	91,8	88,09	60	12	28	0,70				
30	94,8	91,12	60	12	30	0,72				
31	97,9	94,15								
32	100,9	97,17	65	14	30	0,86	80	16	30	1,31
33	103,9	100,20								
34	106,9	103,23	65	14	30	0,92	80	16	30	1,42
35	110,0	106,26	65	14	30	0,94	80	16	30	1,48
36	113,0	109,29	70	16	30	1,05	90	16	30	1,69
37	116,0	112,32	70	16	30	1,09				
38	119,0	115,34	70	16	30	1,08				
39	122,1	118,37								
40	125,1	121,40	70	16	30	1,10	90	16	30	1,90

Please note: Length through bore and bore size may vary from time to time.

