




SPROCKETS AUSTRALIA PTY LTD

SPROCKETS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 40

12,7 x 7,95 mm
Roller 7,95 mm

B1	B2	B3	b1	C	r3
7,2	21,4		7	1,6	13,5



Z	de	dp	Simplex				Duplex			
			dm	D1	A	Kg.	dm	D2	A	Kg.
8	39,3	33,18								
9	43,2	37,13	24	10	25	0,09				
10	47,2	41,10	26	10	25	0,12	28	10	32	0,19
11	51,2	45,07	29	10	25	0,14				
12	55,2	49,07	33	10	28	0,20	35	12	35	0,29
13	59,2	53,06	37	10	28	0,26	38	12	35	0,35
14	63,2	57,07	41	10	28	0,32	42	12	35	0,43
15	67,2	61,09	45	10	28	0,38	46	12	35	0,52
16	71,2	65,10	50	12	28	0,45	50	16	38	0,62
17	75,2	69,11	52	12	28	0,50	54	16	38	0,73
18	79,2	73,14	56	12	28	0,58				
19	83,3	77,16	60	12	28	0,67	62	16	38	0,97
20	87,3	81,19	64	12	28	0,77				
21	91,3	85,22	68	14	28	0,84	70	16	40	1,28
22	95,4	89,24	70	14	28	0,91	70	16	40	1,37
23	99,4	93,27	70	14	28	0,94	70	16	40	1,46
24	103,4	97,29	70	14	28	0,97	75	16	40	1,63
25	107,4	101,33	70	14	28	1,01	80	16	40	1,82
26	111,5	105,36	70	16	30	1,09	85	16	40	2,01
27	115,5	109,40	70	16	30	1,13	85	16	40	2,12
28	119,5	113,42	70	16	30	1,16	90	16	40	2,33
29	123,6	117,46	80	16	30	1,41				
30	127,6	121,50	80	16	30	1,46	100	16	40	2,79
31	131,6	125,54								
32	135,7	129,56	90	16	30	1,78				
33	139,7	133,60								
34	143,8	137,64	90	16	30	1,87				
35	147,8	141,68	90	16	30	1,92	100	16	40	3,40
36	151,8	145,72	90	16	35	2,21				
37	155,9	149,76								
38	159,9	153,80	90	16	35	2,32				
39	163,9	157,83	90	16	35	2,37				
40	168,0	161,87	90	16	35	2,43				

Please note: Length through bore and bore size may vary from time to time.

